

Suban

5 one or more first reproduction units for
reproducing said audio information; and

10 wherein said set information is provided for at
least one of said first reproduction units.

15

sub a2

25

a3
cont

information is to be displayed.

4. An information storage medium according to claim 3, wherein, in a case where the still image information is displayed at the same time when the audio information is reproduced in accordance with the reproduction sequence, the still image information to be displayed first is set as the still image information representing the contents of the reproduction sequence.

50603

5. A method for setting a representative image, wherein the setting method uses an information storage medium for recording audio information, still image information, and management information indicative of a reproduction relationship between said audio information and said still image information, said setting method comprising:

providing one or more first reproduction units for reproducing said audio information which includes first audio information managed in the first reproduction unit;

dividing said first audio information managed in the first reproduction unit into second audio information and third audio information reproduced in the first reproduction unit; and

recording, in said management information, a still image being coincident with the representative image of contents of said first audio information before divided,

as a representative image of contents of said second
audio information and as a representative image of
contents of said third audio information.

6. A method for setting a representative image,
wherein the setting method uses an information storage
medium for recording audio information, still image
information, and management information indicative of a
reproduction relationship between said audio
information and said still image information, said
setting method comprising:

providing one or more first reproduction units for
reproducing said audio information which includes
fourth audio information and fifth audio information
managed in the first reproduction unit;

combining said fourth audio information and said
fifth audio information to form sixth audio information
reproduced in the first reproduction unit; and

recording, in said management information, the
representative image of contents of earlier-reproduced
audio information, as a representative image of
contents of said sixth audio information, wherein said
earlier-reproduced audio information indicates one of
said fourth audio information before combining and said
fifth audio information before combining, which one is
reproduced earlier than the other after combining.

7. A method for setting a representative image,
wherein the setting method uses an information storage

medium for recording audio information, still image information, and management information indicative of a reproduction relationship between said audio information and said still image information, said setting method comprising:

providing a first reproduction unit for reproducing said audio information; and

recording, in said management information, information for specifying or designating the representative image of contents of said audio information reproduced in said first reproduction unit.

8. A method for setting a representative image, wherein one or more first reproduction units for reproducing audio information are used, and the setting method uses an information storage medium for recording audio information, still image information, and set information for setting the still image information to represent contents of at least one of the first reproduction units,

and wherein the still image information to be displayed first in the first reproduction unit is set as the representative image representing the contents of the first reproduction unit.

9. A method for setting a representative image, wherein the setting method uses an information storage medium for recording audio information, still image information, one or more reproduction sequences for

5 and wherein, in a case where the still image
information is displayed at the same time when the
audio information is reproduced in accordance with the
reproduction sequence, the still image information to
be displayed first is set as the representative image
0 representing the contents of the reproduction sequence.

15 still image information, and management information,
said reproducing method comprising:

displaying the one or more searched representative
20 images;

reproducing the selected audio information.

25 information and still image information, said data
structure comprising:

one or more first reproduction units for

set information for setting the still image
information to represent contents of the first
reproduction unit

12. A data structure according to claim 11, wherein the still image information to be displayed first in the first reproduction unit is set as the still image information being representative of the contents of the first reproduction unit.

information for specifying or designating the still image information to represent contents of the reproduction sequence in which the still image information is to be displayed.

14. A data structure according to claim 13,
wherein, in a case where the still image information is
25 displayed at the same time when the audio information
is reproduced in accordance with the reproduction
sequence, the still image information to be displayed

first is set as the still image information
representing the contents of the reproduction sequence.

ADD a4